



## **TECHNICAL DATA SHEET**

| <b>PRODUCT DESCRIPTION</b>                                                                          |               |                        |
|-----------------------------------------------------------------------------------------------------|---------------|------------------------|
| <b>PRODUCT NAME: V8 CVTF</b>                                                                        |               |                        |
| <b>SPECIFICATIONS</b>                                                                               |               |                        |
| <b>CVTF</b>                                                                                         |               |                        |
| <b>TESTS</b>                                                                                        | <b>METHOD</b> | <b>TYPICAL RESULTS</b> |
| APPEARANCE                                                                                          | VISUAL        | Bright & Clear         |
| COLOUR                                                                                              | VISUAL        | GREEN                  |
| DENSITY @ 15°C, g/cm <sup>3</sup>                                                                   | ASTM D1298    | 0.852                  |
| KINEMATIC VISCOSITY @ 40°C, cSt                                                                     | ASTM D445     | 34.3                   |
| KINEMATIC VISCOSITY @ 100°C, cSt                                                                    | ASTM D445     | 7.2                    |
| VISCOSITY INDEX                                                                                     | ASTM D2270    | 180                    |
| FLASH POINT, °C                                                                                     | ASTM D92      | 224                    |
| POUR POINT, °C                                                                                      | ASTM D97      | -45                    |
| Tests has been conducted in accordance with internationally accepted methods such as ASTM standards |               |                        |