



## **TECHNICAL DATA SHEET**

| <b>PRODUCT DESCRIPTION</b>                                                                          |               |                        |
|-----------------------------------------------------------------------------------------------------|---------------|------------------------|
| <b>PRODUCT NAME: V8 DIESEL ENGINE OIL SAE 10W50</b>                                                 |               |                        |
| <b>SPECIFICATIONS</b>                                                                               |               |                        |
| <b>API: CI-4/SL</b>                                                                                 |               |                        |
| <b>TESTS</b>                                                                                        | <b>METHOD</b> | <b>TYPICAL RESULTS</b> |
| APPEARANCE                                                                                          | VISUAL        | Bright & Clear         |
| DENSITY @ 15°C, g/cm <sup>3</sup>                                                                   | ASTM D1298    | 0.856                  |
| KINEMATIC VISCOSITY @ 40°C, cSt                                                                     | ASTM D445     | 142.65                 |
| KINEMATIC VISCOSITY @ 100°C, cSt                                                                    | ASTMD445      | 17.9                   |
| VISCOSITY INDEX                                                                                     | ASTM D2270    | 140                    |
| FLASH POINT, °C                                                                                     | ASTM D92      | Min. 220               |
| POUR POINT, °C                                                                                      | ASTM D97      | -33                    |
| TBN, mgKOH/g                                                                                        | ASTM D2896    | 10.5                   |
| Tests has been conducted in accordance with internationally accepted methods such as ASTM standards |               |                        |